

Optical monitoring of the dust environment at lunar surface exploration sites

R. Lolachi^{1,2,3,*}, D. A. Glenar^{1,2,3}, T. J. Stubbs²

¹ *University of Maryland, Baltimore Co., Baltimore, MD*

² *NASA Goddard Space Flight Center, Greenbelt, MD*

³ *Center for Research and Exploration in Space Science and Technology, NASA/GSFC, Greenbelt, MD*

* Corresponding author: rlolachi@umbc.edu

Abstract. The lunar dust environment and its impact on surface operations during the Artemis era are critical areas of study at this time. Lessons from the Apollo program showed that dust perturbed by human activities on the lunar surface can interfere with the operation of mechanical, thermal and optical systems, in particular the integrity of moving mechanisms and pressure seals¹.

Monitoring the local dust environment during surface activities by measuring the overlying dust loading will be an important capability. This could be accomplished at individual locations using elevated in situ dust detectors; however, a complementary, and arguably more comprehensive, approach would be to measure the intensity of scattered sunlight from dust in the environment surrounding an exploration site.

These measurements can be accomplished using modest cameras and will yield the abundance of dust along an observer line-of-sight. Observations along several look-directions can reveal the dust spatial distribution and can also constrain the average grain size by measuring the angular width of the forward scattering lobe. Perhaps most importantly, these measurements will be able to constrain spatial and temporal variations in dust ejection and deposition rates. Optical measurements of this type can be very sensitive, as demonstrated by the recent detection of faint FUV sunlight scattering by dust in the permanent impact-generated ejecta cloud surrounding the Moon².

Using a precomputed grid of scattering properties for realistically-shaped grains, we simulate spectral intensities for a plausible steady-state dust distribution around an exploration site to assess the feasibility of using commonly available wide-angle optics and commercial off-the-shelf (COTS) image sensors to create a simple notional dust monitoring camera. We model the dust detection sensitivity of cameras constructed using the PL1 (LEIA) image sensor aboard LICIAcube (companion CubeSat on the NASA DART mission)³, as well as sensors available from Hamamatsu and Ximea. Our present dust scattering grid spans UV to near-IR wavelengths and is computed for multiple grain shapes and sizes. Our results indicate that a simple camera can successfully detect a steady-state anthropogenically-raised dust cloud with a peak concentration of $<1 \mu\text{g m}^{-3}$ for a polar site on the Moon—well below what might be expected during surface activities on Artemis missions. Additionally, zodiacal light can be monitored and used as a periodic calibration source⁴.

¹ Gaier, J.R. (2005), NASA/TM—2005-213610.

² Glenar, D.A., et al. (2019), Fall AGU meeting, #P21B-06.

³ Cheng A.F. et al. (2020), *Icarus*, 352, 113989.

⁴ Glenar, D. A. et al. (2014), *JGR Planets*, 119, 2548–2567.