

To investigate the lunar environment and surface interactions

5

<u>Stas Barabash</u>¹ Yoshifumi Futaana¹ and the SELMA Team

¹Swedish Institute of Space Physics Kiruna, Sweden

DAP, Boulder, January, 2017

SELMA core team

Instrument Principal Investigato	rs	
M. Wieser (ENAT, LSHE)	+-	Swedish Institute of Space Physics, Kiruna, Sweden (IRF-K)
P. Wurz (LEMS)	•	University of Bern, Bern, Switzerland (UBe)
U. Mall (VIS-NIR)		Max Planck Institute for Solar System Research, Göttingen, Germany (MPS)
N. Andre (LIS)		IRAP- Université de Toulouse, CNRS, France (IRAP)
N. Ivchenko (IPMAG)	-	KTH Royal Institute of Technology, Stockholm, Sweden (KTH)
J. Oberst (SPOSH)		German Aerospace Center, Berlin, Germany (DLR)
K. Retherford (MUVS)		Southwest Research Institute, San Antonio, USA (SwRI)
A. Coates (LES, IPEI)		Mullard Space Science Laboratory, University College London, London, UK (MSSL)
A. Masters (MMAG)		Imperial College London, London, UK (ICL)
JE. Wahlund (Orchestra, MiniEF)	-	Swedish Institute of Space Physics, Uppsala, Sweden (IRF-U)
M. Horanyi (LDD)		Laboratory for Atmospheric and Space Physics, University of Colorado, USA (LASP)
E. Kallio (IPCAM, IECAM)	+	Aalto University, Helsinki, Finland (AU)

SELMA (Surface, Environment, Lunar Magnetic Anomalies) is a medium class (costs for ESA < 550 MEUR) interdisciplinary lunar mission focused to study how the lunar environment interacts with the surface

SELMA science questions


- What is the origin of water on the Moon?
- How do the "volatile cycles" on the Moon work?
- How do the lunar mini-magnetospheres work?
- What is the influence of dust on the lunar environment and surface?

SELMA specific features:

- combination of remote sensing via UV, IR, and energetic neutral atoms (ENA) and in-situ measurements of fields, waves, plasma, exospheric gasses, and dust;
- Dedicated impact experiment to investigate volatile content in the soil of the permanently shadowed area of the Shackleton crater;
- Dedicated impact probe to sound the Reiner-Gamma minimagnetosphere and its interaction with the surface




- Possible sources of OH/H₂O in the regolith (100-1000 ppm) and the permanently shadowed areas (a few %)
 - Comets/Meteoroids
 - Solar wind
- The nanophase metallic Fe of the lunar soil reacts with implanted protons and the reactions in the solid state result in water release (*Gibson and Moore*, 1972). Water molecules remain in minerals but some are evaporated and trapped in cold traps.
- SELMA focuses on the role of the solar wind





- Water content and correlation with the impinging proton flux
 - Mapping of the lunar surface in the 2.7 3.4 μ m IR absorption band to identify the presence of OH/H₂O.
 - Mapping of the lunar surface in the FUV reflection band to identify the presence of frost and surface hydration
 - Mapping of the proton precipitation via backscattered hydrogen
- Water transport
 - Hydrogen density along the orbit (exospheric mass spectrometer)




IR mapping (Chandrayaan-1, ; *Pieters et al., 2010)*

Backscattered hydrogen map of the Aitken basin (Chandrayaan-1, *Vorburger et al, 201*5)




- Water content in the regolith of the permanently shadowed area (Shackleton crater)
 - Passive 10 kg copper impact probe will release up to 40 kg water (*Holsapple and Housen model*) impacting a crater wall
 - SELMA flies through the plume for direct water measurements (up to 10 sec) including isotope (D/H) measurements.






- Establish variability, sources and sinks of the lunar exosphere
 - Solar wind results in atom sputtering populating the exosphere with the lunar surface material such as Si, Ti, Al, Fe, Mg, Ca, and O
 - Solar wind is a potential source of noble gasses. The solar wind ions are absorbed, trapped and then released into the exosphere
- Investigate how the lunar exosphere content is related to impact events
- Measurements of the lunar exosphere composition, profile, and variability simultaneously with the solar wind, dust, meteoride and artificial impacts
- Measurements of the ionized species H₂+, He+,
 C+, O+, Na+, Al+, Si+, K+, Ar+, Ca+ and Fe+,




Density profiles for species related to solar wind irradiation (*Wurz et al., 2012*)




- Surface magnetic fields up to 30...100 nT over a region of 100 km result in an unusual range of plasma parameters
 - Electrons magnetized (*r_e*~100 m, for *T_e*~10 eV, *B* ~ 30 nT)
 - Protons un-magnetized ($r_p \sim 100$ km, for $E_p \sim 800$ eV, $B \sim 30$ nT).
- Chandrayaan-1 ion analyzer showed the strongest anomalies reflect up to 50% of the impinging solar wind (Lue et al.. 2011)
- Solar wind voids/depletions (minimagnetospheres) are formed due to ambipolar electric field
 - Electron physics defines the minimagnetosphere structure: a scale of r_e~100 m
- Unique plasma laboratory to understand small scale interactions in the solar system








- SELMA carries a dedicated probe to flythrough an isolated magnetic anomaly at Reiner – gamma crater
 - High-time resolution (500 mks) plasma, field and wave measurements for 30 min before the impact
- The magnetic anomalies correlate with specific albedo features, swirls (*Hood et al.,* 2001)
 - Correlation of ENA and IR/Far-UV maps in the anomaly region to investigate the effects of the mini-magnetospheres on space weathering






Q4: The influence of dust on the environment and surface? (1)

- SELMA will characterize the lunar dust exosphere up to the Pole (LANDEE measurements cover ±22° latitude range).
- The key SELMA measurements is how the impact events affect the lunar dust exosphere
 - Simultaneous monitoring of the meteoroid impact (> 100 g) and the lunar dust environment
- SELMA will study how the plasma effects results in lofting the lunar dust
 - Simultaneous dust and plasma/wave measurements



Dust density (> 0.3 mkm) from LANDEE (Horanayi et al., 2015)






Remote sensing instruments	In-situ instruments
Infrared and visible spectrometer	Lunar ion spectrometer
Spectral range 400 – 3600 nm	M/DM > 80
Wide angle and transient phenomena camera	Lunar scattered proton and negative ion
Visible, FoV 120 x60 °	experiment:
Meteoroid impact (>100 g)	Energy range: 10 eV – 10 keV
Moon UV imaging spectrometer	Lunar electron spectrometer
Spectral range 115 - 315 nm	
ENA telescope	Moon magnetometer
Energy range $10 \ eV - 3 \ keV$	
Angular resolution $< 10^{\circ}$	
SELMA Impact Probe for Magnetic Anomaly	Lunar exospheric mass spectrometer:
sounding (SIP-MA)	M/DM > 1000
Waves and electric field instrument	Plasma wave instrument
Impact probe ions and electrons spectrometer	Lunar dust detector: M>10 ⁻¹⁵ kg
Time res. $< 0.5 \text{ s/3D}$	
Impact probe magnetometer	Passive 10 kg copper spherical impactor
Context camera	




- Launch January 1, 2029 (flexible) by Souyz-Fregat or Ariane 62.
- Direct transfer to Moon and insertion on the quasi-frozen 30 x 200 km, polar orbit, ~2 hr orbital period
 - Pericenter at south pole
- Release of the impact probe to sound the Reiner-Gamma magnetic anomaly 6 months after launch;
 - Probe operates for 35 minutes






Mission overview (2)

- At the end of the mission the passive impactor impacts the permanently shadowed region of the Shackleton crater >10 sec before SELMA
- SELMA orbiter flies through the resulted plume.
- The data are downlinked to ground and 6U Relay CubeSat. The Cubesat stays on orbit for 2 hours more to downlink the complete data set.
 - The last 10 sec before the impact no direct visibility from the ground
- Nominal mission 15 months








٠

SELMA orbiter uses a common 3-x Relay 6U CubeSat stabilized nadir pointing platform 627 kg dry-mass 10 kg copper impactor 111 kg payload 42 kg impact probe for the magnetic anomaly studies (SIP-MA) Passive 10 kg copper impact 6U Rekay CubeSat Total mass at launch 1302 kg Specific requirements includes: EMC and cleanliness program **SELMA** orbiter **SELMA** Impact Probe Magnetic Anomaly




- SIP-MA is 42 kg 3-x stabilized free-flyer carrying 8.2 kg payload.
- SIP-MA powered by batteries operates only for about 30 min before the impact.
- SIP-MA communicates with the SELMA orbiter via one-way 1 Mbps link.
- RCS is a 6U CubeSat equipped with a Sband communication package and a simple camera to monitor the SELMA impact







- SELMA is a unique mission to investigate the complex environment surface interaction at the Moon.
- No missions with similar objectives and payloads were, are, or will be conducted or planned in the nearest future.



ESA S-class:2012, ~50 M€



ESA M-class, 2016, ~500M€





- ESA M-class missions selection in June 2017:
 1-3 missions for further studies
- Support SELMA
 - Open http://tinyurl.com/m5-selma-supporter
 - Type your name, institution, and country
 - Click "Submit"
 - · Send the link to your friends

SELMA supporte	-
for-m5-missions) a mission to the Moon to	on opportunity call (<u>http://www.cosmos.esa.int/web/</u> o investigate its environment was proposed in Octor
2016: SELMA. Thank you very much for you who already	expressed the support of SELMA
Even after the close of the call itself, we de appreciate that you could support this mis	ecided to continue gathering supporters. We really sion by registering the following form.
Any questions regarding SELMA mission a (Science Lead of SELMA).	and the suporters can be sent to Dr Yoshifumi Futaar
*Obligatorisk	
Name *	
Ditt svar	
Institution *	
Ditt svar	
Country *	
-	
Ditt svar	
Message (optional)	
Ditt svar	
Please click the "submit" button. Your in Thank you for your support!	nformation will be sent to the SELMA proposal te
SKICKA	

http://tinyurl.com/m5-selma-supporter